# Joint Crediting Mechanism Approved Methodology CL\_AM001 "Installation of Solar PV System"

## A. Title of the methodology

Installation of Solar PV System, Version 0102.0

### **B.** Terms and definitions

Terms	Definitions
Solar photovoltaic (PV) system	An electricity generation system which converts sunlight
	into electricity by the use of photovoltaic (PV) modules. The
	system also includes ancillary equipment such as inverters
	required to change the electrical current from direct current
	(DC) to alternating current (AC).

## C. Summary of the methodology

Items	Summary
GHG emission reduction	Displacement of grid electricity and/or captive electricity using
measures	fossil fuel as power source by installation and operation of the
	solar PV system(s).
Calculation of reference	Reference emissions are calculated on the basis of the AC
emissions	output of the solar PV system(s) multiplied by either; 1)
	conservative emission factor of the grid, or 2) conservative
	emission factor of the captive diesel power generator.
Calculation of project	Project emissions are the emissions from the solar PV
emissions	system(s), which are assumed to be zero.
Monitoring parameters	The quantity of the electricity generated by the project solar PV
	system(s)

### D. Eligibility criteria

This methodology is applicable to projects that satisfy all of the following criteria.

Criterion 1	The project newly installs solar PV system(s).	
Criterion 2	The PV modules are certified for design qualifications (IEC 61215, IEC 61646	
	or IEC 62108) and safety qualification (IEC 61730-1 and IEC 61730-2).	
Criterion 3	The equipment used for monitoring output power of the solar PV system(s)	
	and irradiance is installed at the project site.	

### E. Emission Sources and GHG types

Reference emissions	
Emission sources GHG types	
Consumption of grid and/or captive electricity CO <sub>2</sub>	
Project emissions	
Emission sources GHG type	
Generation of electricity from solar PV system(s) N/A	

#### F. Establishment and calculation of reference emissions

#### F.1. Establishment of reference emissions

The default emission factor is set in a conservative manner for the Chilean regional grids: the Central InterconnectedNational Electricity System (SIC), the Northern Interconnected System (SINGSEN), the Aysén system, and the Magallanes system.

The emission factor is calculated based on the conservative operating margin that reflects on the latest electricity mix including low cost/must run resources for each regional grid in Chile during 2014-2016-2018 and refers to the conservative emission factor of each fossil fuel power plant in order to secure net emission reductions. The conservative emission factor of each plant is calculated to be 0.826 tCO<sub>2</sub>/MWh for coal-fired power plant and 0.364 tCO<sub>2</sub>/MWh for gas-fired power plant based on the survey on heat efficiency of power plant in Chile. The emission factor for diesel power plant is calculated to be 0.533 tCO<sub>2</sub>/MWh based on a default heat efficiency of 49%, an efficiency level which is above the value of the world's leading diesel power generators.

In case the <u>solar</u> PV system(s) in a proposed project activity is directly connected or connected via an internal grid, not connecting to a captive power generator, to a regional grid (PV Case

1), the value of operating margin including LCMR resources, using the best heat efficiency among currently operational plants in Chile in calculating emission factors of fossil fuel power plants, areis applied. The emission factors to be applied in this case are shown as "PV Case 1" in section I of this methodology.

In the case the <u>solar</u> PV system(s) in a proposed project activity is connected to an internal grid connecting to both a regional grid and a captive power generator (PV Case 2), the lower value between emission factors shown as "PV Case 1" in section I of this methodology and the conservative emission factor of diesel-fired power plant of 0.533 tCO<sub>2</sub>/MWh is applied. The emission factors to be applied in this case are shown as "PV Case 2" in section I of this methodology.

In the case that the <u>solar PV</u> system(s) in a proposed project activity is <u>only</u>-connected to an internal grid <u>only</u> connecting to a captive power generator (PV Case 3), the emission factor of a diesel generator calculated by applying the heat efficiency of 49%, an efficiency level which is above the value of the world's leading diesel generator, which is set to 0.533 tCO<sub>2</sub>/MWh, is applied.

The emission factors to be applied in each case are shown in Section I. Data and parameters fixed ex ante of this methodology.

### F.2. Calculation of reference emissions

$$\mathrm{RE}_p = \sum_{i} (EG_{i,p} \times EF_{RE,i})$$

- $RE_p$  : Reference emissions during the period p [tCO<sub>2</sub>/p]
- $EG_{i,p}$ : Quantity of the electricity generated by the project solar PV system *i* during the period *p* [MWh/p]
- $EF_{RE,i}$ : Reference emission factor of the project solar PV system *i* [tCO<sub>2</sub>/MWh]

## G. Calculation of project emissions

 $PE_p = 0$ 

## H. Calculation of emissions reductions

$ER_p$	$= RE_p - PE_p$
	$= RE_p$
$\mathrm{ER}_{\mathrm{p}}$	: Emission reductions during the period $p$ [tCO <sub>2</sub> /p]
$RE_p$	: Reference emissions during the period $p$ [tCO <sub>2</sub> /p]
$PE_p$	: Project emissions during the period $p$ [tCO <sub>2</sub> /p]

### I. Data and parameters fixed *ex ante*

The source of each data and parameter fixed *ex ante* is listed as below.

Parameter	Description of data	Source
$EF_{RE,i}$	Reference emission factor of the regional grid	Additional information
	and/or captive power generator which is displaced	The default emission
	by the project solar PV system $i$ .	factor is obtained from a
	The value for FE is calented from the list of	study of electricity
	The value for $EF_{RE,i}$ is selected from the list of	systems in Chile and the
	emission factors in the following manner:	most efficient diesel
	PV Case 1: In case the solar PV system(s) in a	power generator (49%
	proposed project activity is connected to a regional	heat efficiency).
	grid including through internal grid which is not	
	connected to a captive power generator, $\mathrm{EF}_{\mathrm{RE},\mathrm{i}}$ is	The default value is
	set as follows per the connected regional grid:	revised if deemed
		necessary by the JC.
	Regional grid name: Emission factor for PV Case 1:	
	SIC (CentralSEN 0.314404 tCO <sub>2</sub> /MWh	
	(National System) SING (Northern System) 0.718 tCO <sub>2</sub> /MWh	
	Since (Normenn System) $0.718 \text{ tCO}_2\text{/MWh}$ Aysén System $0.200176$ tCO_2/MWh	
	Magallanes System 0.361 tCO <sub>2</sub> /MWh	
	<u>PV Case 2:</u> In case the <u>solar</u> PV system(s) in a	
	proposed project activity is connected to an internal	
	grid connected to both a regional grid and a captive	

power generator, $EF_{RE,i}$ is set as follows per the	
connected regional grid:	
connected regional grid.	
Regional grid name:Emission factor for PV Case 2:SIC (CentralSEN (National System)0.314404 tCO2/MWh 0.533 tCO2/MWh 0.200176 tCO2/MWh 0.361 tCO2/MWh	
<u>PV Case 3:</u> In case the <u>solar</u> PV system(s) in a proposed project activity is connected to an internal grid which is not connected to the regional grid, $EF_{RE,i}$ is set at 0.533 tCO <sub>2</sub> /MWh.	

## History of the document

Version	Date	Contents revised
01.0	19 December 2017	JC2, Annex 5
		Initial approval.
<u>02.0</u>	<u>4 December 2020</u>	Electronic decision by the Joint Committee
		• Updated the reference emission factors of regional grids
		in accordance with the integration of the regional grids
		of SIC and SING into SEN.
		• <u>Corrected some wordings.</u>