

### JCM Proposed Methodology Form

#### Cover sheet of the Proposed Methodology Form

Form for submitting the proposed methodology

Host Country	Republic of Indonesia
Name of the methodology proponents submitting this form	Azbil Corporation
Sectoral scope(s) to which the Proposed Methodology applies	3. Energy demand
Title of the proposed methodology, and version number	GHG emission reductions through optimization of boiler operation in Indonesia, ver.1.0
List of documents to be attached to this form (please check):	<input type="checkbox"/> The attached draft JCM-PDD: <input checked="" type="checkbox"/> Additional information
Date of completion	08/10/2014

History of the proposed methodology

Version	Date	Contents revised
1.0	08/10/2014	First edition

### A. Title of the methodology

GHG emission reductions through optimization of utility system operation in Indonesia, ver 1.0

### B. Terms and definitions

Terms	Definitions
Utility Facility Operation Optimization Technology	Technology to optimize the operation of existing utility facilities such as boilers through application of software algorithm using linear programming method.

### C. Summary of the methodology

Items	Summary
<i>GHG emission reduction measures</i>	The project achieves energy conservation in boilers, through operation optimization by applying Utility Facility Operation Optimization Technology.
<i>Calculation of reference emissions</i>	Reference emissions are calculated on the basis of monitored project steam generation and specific CO <sub>2</sub> emissions per steam generated, through analysis of historical relationship between steam generation and fuel consumption of boilers.
<i>Calculation of project emissions</i>	Project emissions are calculated on the basis of monitored fuel consumption and emission factor of fuel consumed after implementation of the project.
<i>Monitoring parameters</i>	Energy consumption and steam generation in boilers.

**D. Eligibility criteria**

This methodology is applicable to projects that satisfy all of the following criteria.

Criterion 1	The project is implementation of operation optimization of boilers to generate steam, through introduction of Utility Facility Operation Optimization Technology.
Criterion 2	The site of introduction is an existing industrial facility which includes two or more boilers to generate steam.
Criterion 3	Historical data for energy consumption and generation of steam is obtainable for individual boiler.
Criterion 4	All steam demand is met internally and not sourced from outside the industrial facility.

**E. Emission Sources and GHG types**

Reference emissions	
Emission sources	GHG types
Emissions from fossil fuel consumption by boilers	CO <sub>2</sub>
Project emissions	
Emission sources	GHG types
Emissions from fossil fuel consumption for by boilers	CO <sub>2</sub>

## F. Establishment and calculation of reference emissions

### F.1. Establishment of reference emissions

Reference emissions are calculated under the assumption that the current boilers continue to be used. When new boilers are introduced to substitute existing boilers or as capacity expansion, procedure to recalculate reference emissions is provided.

In order to establish reference emissions, CO<sub>2</sub> emissions are calculated on the basis of regression obtained through regression analysis of historical CO<sub>2</sub> emissions, with historical steam generation as variables.

#### Ensuring net emission reductions

The methodology ensures conservativeness by not including the associated reduction of fuel for auxiliary equipments (e.g. fans and pumps) which is expected to occur as a result of the project. Furthermore, the methodology ensures net reduction by adopting a conservative assumption when boilers are replaced.

### F.2. Calculation of reference emissions

#### Step 1. Calculation of historical emissions

Historical emissions are calculated as follows:

- Obtain data on hourly fuel consumption for the historical period of one year preceding introduction of Utility Facility Operation Optimization Technology up to the period not earlier than 6 months before submission of the draft PDD.
- Calculate hourly CO<sub>2</sub> emissions according to the following formulae.

$$HE_{j,xh} = \sum_i (FC_{i,j,xh} \times NCV_i \times EF_i) \quad (1)$$

$$HE_{xh} = \sum_j HE_{j,xh} \quad (2)$$

Where

$HE_{xh}$  = Historical CO<sub>2</sub> emissions on hour  $h$  in the historical 1-year period  $x$ . [tCO<sub>2</sub>]

$HE_{j,xh}$  = Historical CO<sub>2</sub> emissions from boiler  $j$  on hour  $h$  in the historical 1-year period  $x$ . [tCO<sub>2</sub>]

$FC_{i,j,xh}$  = Consumption of fossil fuel  $i$  by the boiler  $j$  on hour  $h$  in the historical 1-year period  $x$ . [mass or volume unit]

$NCV_i$	=	Net calorific value of fossil fuel type $i$ . [ GJ/mass or volume unit]
$EF_i$	=	CO <sub>2</sub> emission factor of fossil fuel type $i$ . [tCO <sub>2</sub> /GJ]

### Step 2. Regression analysis

Plot the data with hourly data of historical steam generation by the boilers ( $ST_{xh}$ ) on the  $x$ -axis and hourly total CO<sub>2</sub> emissions by the boilers ( $HE_{xh}$ ) on the  $y$ -axis. Omit data obtained during periods of startup, shutdown, maintenance or malfunction of equipment or measurement device, and periods of operating outside the operating range specified by the project participants or by the equipment manufacturer.

Perform a linear regression analysis. If the regression coefficient  $R^2$  of the plotted data is smaller than 0.49, omit statistical outliers with a plot outside 2 times the standard deviation from the regression line.

Repeat the process until the  $R^2$  of the plotted data is larger than 0.49. Perform a linear regression analysis with the remaining data to derive a linear regression equation as follows

$$HE_{xh} = a \times ST_{xh} + b \quad (3)$$

Where

$HE_{xh}$	=	Historical CO <sub>2</sub> emissions from boilers on hour $h$ in the historical 1-year period $x$ . [tCO <sub>2</sub> ]
$ST_{xh}$	=	Historical steam generation by the boilers on hour $h$ in the historical 1-year period $x$ . [tonnes steam]
$a, b$	=	Parameters derived as a result of linear regression analysis. [dimensionless]

If the resulting regression coefficient  $R^2$  remains below 0.49 as a result of the analysis, then conduct the following procedure.

- Perform regression analysis for individual boiler for the same historical 1-year period  $x$ . Obtain regression coefficient  $R$  for each boiler by using the same procedure as stated above.
- Identify boilers which resulted in the resulting regression coefficient  $R^2$  is lower than 0.49. For such boiler, re-calibrate measurement equipments attached to the boiler (fuel flow meters, steam flow meters). Conduct a one-month campaign without operating the Utility Facility Operation Optimization Technology. Perform a linear regression analysis based on

the data obtained during the one-month campaign, by using the same procedure as stated above, to yield a regression equation as follows:

$$HE_{j,ch} = a_j \times ST_{j,ch} + b_j \quad (4)$$

Where

$$HE_{j,ch} = \sum_i (FC_{i,j,ch} \times NCV_i \times EF_i) \quad (5)$$

$HE_{j,ch}$  = Historical CO<sub>2</sub> emissions from the boiler  $j$  on hour  $h$  in the one-month campaign  $c$ . [tCO<sub>2</sub>]

$ST_{j,ch}$  = Historical steam generation by the boiler  $j$  on hour  $h$  in the one-month campaign  $c$ . [tonnes steam]

$a_j, b_j$  = Parameters derived as a result of linear multivariate regression analysis for individual boiler  $j$  based on the data obtained in the one-month campaign.

$FC_{i,j,ch}$  = Consumption of fuel  $i$  by the boiler  $j$  on hour  $h$  in the one-month campaign  $c$ .

$NCV_i$  = Net calorific value of fossil fuel type  $i$ . [GJ/mass or volume unit]

$EF_i$  = CO<sub>2</sub> emission factor of fossil fuel type  $i$ . [tCO<sub>2</sub>/GJ]

- Re-perform steps 1 and 2 but by substituting for the boiler which has conducted the campaign,  $ST_{j,xh}$  by  $[(HE_{j,xh} - b_j) / a_j]$  for cases where only steam flow meters are found to be deficient, and  $HE_{j,xh}$  by  $(a_j \times ST_{j,xh} + b_j)$  in all other cases.  $ST_{j,xh}$  is the historical steam generation by the boiler  $j$  on hour  $h$  in the historical 1-year period  $x$ .
- If the regression coefficient  $R^2$  of the regression analysis according to step 2 with the adjusted data is still below 0.49, the methodology is not applicable.

### Step 3. Calculation of reference emissions

Reference emissions are calculated as follows:

$$RE_p = \sum_h (a \times ST_{p,h} + b) \quad (6)$$

Where

$RE_p$  = Reference emissions during a given time period  $p$ . [tCO<sub>2</sub>/p]

$ST_{p,h}$  = Process steam generation on hour  $h$  during the time period  $p$ . [tonnes steam/p]

$a, b$  = Parameters derived as a result of linear regression analysis as described in step 2

**Annex: Provisions for recalculation of reference emissions when new boilers are introduced.**

When new boilers are introduced, reference emissions obtained as above are no longer valid, and need to be recalculated under the following procedure. To undergo this procedure, historical data for energy consumption and generation of each boiler is required. The procedure applies to cases when new boilers replace existing boilers, and when new boilers are introduced to provide additional capacity.

**Step i: Calculate historical CO<sub>2</sub> emissions on hour  $h$  in the historical period  $x$  for all existing boilers.**

The calculation is conducted according to the following equation.

$$HE_{j,xh} = \sum_i FC_{i,j,xh} \times NCV_i \times EF_i \quad (7)$$

Where

$HE_{j,xh}$  = Historical CO<sub>2</sub> emissions from the boiler  $j$  on hour  $h$  in the historical 1-year period  $x$ . [tCO<sub>2</sub>]

$FC_{i,j,xh}$  = Consumption of fuel  $i$  by the boiler  $j$  on hour  $h$  in the historical 1-year period  $x$ . [mass or volume unit]

$NCV_i$  = Net calorific value of fossil fuel type  $i$ . [GJ/mass or volume unit]

$EF_i$  = CO<sub>2</sub> emission factor of fossil fuel type  $i$ . [tCO<sub>2</sub>/GJ]

**Step ii: Calculate design CO<sub>2</sub> emission factor of existing boiler**

For each existing boiler, calculate its design CO<sub>2</sub> emission factor as follows

$$EF_j = \frac{EF_{i,j}}{\eta_j} \quad (8)$$

Where

$EF_j$  = Design CO<sub>2</sub> emission factor of boiler  $j$ . [tCO<sub>2</sub>/GJ-steam]

$EF_{i,j}$  = CO<sub>2</sub> emission factor of the main fuel  $i$  consumed by boiler  $j$ . [tCO<sub>2</sub>/GJ-fuel]

$\eta_j$  = Design efficiency of existing boiler  $j$ . [dimensionless][GJ-fuel/ GJ-steam]

For boilers providing the same utility as the new boiler, rank each existing boiler according to the descending order of design CO<sub>2</sub> emission factor.

**Step iii: Adjust CO<sub>2</sub> emission factor of existing boiler ( $HE_{j,xh}$ )**

Adjust CO<sub>2</sub> emission factor of existing boiler ( $HE_{j,xh}$ ), starting from the existing boiler whose design CO<sub>2</sub> emission factor is highest, up to the theoretical maximum amount of utility that can be provided by the new boiler (assuming a capacity factor of 100%), as follows:

$$HE_{adj,j,xh} = HE_{j,xh} \times \min \left( \frac{EF_{new}}{EF_j}, 1 \right)$$

(9)

Where  $EF_{new}$  is  $EF_j$  for the new boiler.

**Step iv: Recalculate  $H_{x,h}$** 

Recalculate  $H_{x,h}$  as follows:

$$HE_{adj,xh} = \sum_j HE_{adj,j,xh} \quad (10)$$

**Step v: Recalculate the regression analysis**

Linear multivariate regression analysis as described in step 2 is recalculated, using  $HE_{adj,xh}$  obtained above instead of  $HE_{x,h}$ .

When boilers are introduced during the 1-year historical period, undergo the recalculation steps i and ii for the period before introduction of new boilers.

**G. Calculation of project emissions**

Project emissions are calculated on the basis of monitored electricity and fuel consumption.

$$PE_p = \sum_i (FC_{i,p} \times NCV_i \times EF_i) \quad (11)$$

Where

$PE_p$	=	Project emissions during a given time period $p$ . [tCO <sub>2</sub> /p]
$FC_{i,p}$	=	Consumption of fossil fuel $i$ by the boiler during the time period $p$ . [mass or volume unit/p]
$NCV_i$	=	Net calorific value of fossil fuel type $i$ . [GJ/mass or volume unit]
$EF_i$	=	CO <sub>2</sub> emission factor of fossil fuel type $i$ . [tCO <sub>2</sub> /GJ]

**H. Calculation of emissions reductions**

Emission reductions are calculated as the difference between the reference level (crediting threshold) and project emissions, as follows.

$$ER_p = RE_p - PE_p \quad (12)$$

Where

$ER_p$  = Emission reductions during the time period  $p$ . [tCO<sub>2</sub>/p]

$RE_p$  = Reference emissions during the time period  $p$ . [tCO<sub>2</sub>/p]

$PE_p$  = Project emissions during the time period  $p$ . [tCO<sub>2</sub>/p]

## I. Data and parameters fixed *ex ante*

The source of each data and parameter fixed *ex ante* is listed as below.

Parameter	Description of data	Source
$FC_{i,j,xh}$	Consumption of fuel $i$ by the boiler $j$ on hour $h$ in the historical 1-year period $x$ .	Site record.
$FC_{i,j,ch}$	Consumption of fuel $i$ by the boiler $j$ on hour $h$ in the one-month campaign $c$ .	Site record.
$NCV_i$	Net calorific value of fossil fuel type $i$ .	In the order of preference: a) values provided by the fuel supplier; b) measurement by the project participants; c) regional or national default values; d) IPCC default values provided in table 1.2 of Ch.1 Vol.2 of 2006 IPCC Guidelines on National GHG Inventories.
$EF_i$	CO <sub>2</sub> emission factor of fossil fuel type $i$ .	In the order of preference: a) values provided by the fuel supplier; b) measurement by the project participants; c) regional or national default values; d) IPCC default values provided in table 1.4 of Ch.1 Vol.2 of 2006 IPCC Guidelines on National GHG Inventories.
$ST_{xh}$	Historical steam generation by the boilers on hour $h$ in the historical 1-year period $x$ .	Site record.
$ST_{j,ch}$	Historical steam generation by the boiler $j$ on hour $h$ in the one-month	Site record.

	campaign $c$ .	
$ST_{j,sh}$	Historical steam generation by the boilers $j$ on hour $h$ in the historical 1-year period $x$ .	Site record.
$a, b$	Parameters derived as a result of linear multivariate regression analysis.	Calculated according to step 2 in section F2.
$a_j, b_j$	Parameters derived as a result of linear multivariate regression analysis.	Calculated according to step 2 in section F2.