# Joint Crediting Mechanism Approved Methodology TH\_AM001 "Installation of Solar PV System"

# A. Title of the methodology

Installation of Solar PV System, Ver 03.0

### B. Terms and definitions

Terms	Definitions
Solar photovoltaic (PV) system	An electricity generation system which converts sunlight
	into electricity by the use of photovoltaic (PV) modules.
	The system also includes ancillary equipment such as
	inverters required to change the electrical current from
	direct current (DC) to alternating current (AC).

# C. Summary of the methodology

Items	Summary
GHG emission reduction	Displacement of grid electricity and/or captive electricity using
measures	fossil fuel as power source by installation and operation of the
	solar PV system(s)
Calculation of reference	Reference emissions are calculated on the basis of the AC
emissions	output of the solar PV system(s) multiplied by the conservative
	emission factor of grid electricity and/or captive electricity.
Calculation of project	Project emissions are the emissions from the solar PV
emissions	system(s), which are assumed to be zero.
Monitoring parameters	The quantity of the electricity generated by the project solar PV
	system(s)

# D. Eligibility criteria

This methodology is applicable to projects that satisfy all of the following criteria.

Criterion 1 The project installs solar PV system(s).	Criterion 1	The project installs solar PV system(s).
--	-------------	--

Criterion 2	The solar PV system is connected to the internal power grid of the project site
	and/or to the grid for displacing grid electricity and/or captive electricity at the
	project site.
Criterion 3	The PV modules have obtained a certification of design qualifications (IEC
	61215, IEC 61646 or IEC 62108) and safety qualification (IEC 61730-1 and
	IEC 61730-2).
Criterion 4	The equipment to monitor output power of the solar PV system and irradiance
	is installed at the project site.

### E. Emission Sources and GHG types

Reference emissions		
Emission sources GHG types		
Consumption of grid and/or captive electricity CO <sub>2</sub>		
Project emissions		
Emission sources GHG types		
Generation of electricity from solar PV system(s) N/A		

#### F. Establishment and calculation of reference emissions

### F.1. Establishment of reference emissions

The emission factor of the Thai grid published by the government is 0.5251 tCO<sub>2</sub>eq/MWh (combined margin, 2021).

More than 53.6% of the grid power is derived from natural gas in Thailand. Considering that it is difficult to identify which of the natural gas-fired power plants is displaced by the project solar PV system(s), the grid emission factor is established by assuming that the most efficient natural gas-fired power plant in Thailand is displaced in conservative manner, which will lead to ensuring net emission reductions. The grid emission factor is set to be 0.305 tCO<sub>2</sub>eq/MWh which corresponds to the most efficient natural gas-fired power plant in Thailand (generation efficiency: 64.1%).

#### F.2. Calculation of reference emissions

$$RE_p = \sum_{i} EG_{i,p} \times EF_{RE}$$

RE<sub>p</sub> : Reference emissions during the period p [tCO<sub>2</sub>eq/p]

 $EG_{i,p}$ : Quantity of the electricity generated by the project solar PV system i during the

period *p* [MWh/p]

EF<sub>RE</sub> : Reference CO<sub>2</sub> emission factor of grid electricity and/or captive electricity

[tCO<sub>2</sub>eq/MWh]

### G. Calculation of project emissions

 $PE_p = 0$ 

PE<sub>p</sub> : Project emissions during the period p [tCO<sub>2</sub>eq/p]

### H. Calculation of emissions reductions

$$ER_{p} = RE_{p} - PE_{p}$$
$$= RE_{p}$$

 $ER_p$ : Emission reductions during the period p [tCO<sub>2</sub>eq/p]  $RE_p$ : Reference emissions during the period p [tCO<sub>2</sub>eq/p]  $PE_p$ : Project emissions during the period p [tCO<sub>2</sub>eq/p]

#### I. Data and parameters fixed ex ante

The source of each data and parameter fixed ex ante is listed as below.

Parameter	Description of data	Source
EF <sub>RE</sub>	Reference CO <sub>2</sub> emission factor of grid and/or	Additional information
	captive electricity, calculated based on the	The default emission factor is
	power generation efficiency of 64.1% using	derived from the result of the
	natural gas as the power source.	survey on the generation

The default value for EF <sub>RE</sub> is set to be 0.305	efficiency of major natural
tCO <sub>2</sub> eq/MWh.	gas-fired power plants in
	Thailand. The default value
	should be revised if necessary
	from survey result which is
	conducted by the JC or project
	participants.

# History of the document

Version	Date	Contents revised
03.0	14 July 2025	Electronic decision by the Joint Committee.
		Revision to:
		Update the reference emission factor based on the national
		grid to ensure conservativeness and net emission
		reductions
02.0	28 September 2020	Electronic decision by the Joint Committee.
		Revision to:
		Change the description of "Measurement methods and
		procedures" to clarify the requirement for calibration in
		the Monitoring Spreadsheet: JCM_TH_AM001
01.0	23 August 2016	Decision by the Joint Committee.
		Initial approval.